

optisan[®]
Japan's Secret Optics



Cobra SERIES

Out-performs its price

Cobra SERIES

Out-performs its price

Designed as a budget scope but with all the features required for hunting, plinking and even Hunter Field Target Competition.

Optical Performance

Astonishing performance in low light condition makes the Cobra well suited for general hunting.

Rugged Build In A One-piece Tube Construction

Built with 1 inch one-piece tube with in-house sealing technique to ensure consistent optical quality and repeatability. The Cobra is built with a sealed one piece tube to ensure an unbelievable level of shockproofing and reliability.

Firm Finger-adjustable Turret

Finger adjustable under a low cover, smooth and precise and they do the job perfectly.

Operational Environment Tested

Waterproof testing with W/E cap-off, at 50°C, 0.5m water depth for 10 minutes shows no leakage.
Fogproof testing also with cap-off, Condensation disappears within 1 minutes after placing in -10°C for 30 mins.

Smooth and Precise Objective Parallax Adjustment

The front parallax is smooth and clearly marked.

Value Pack

Standard package includes:
Good quality 1 inch mounts
Transparent flip-up covers

This scope is for those who have a job to do, and want a simple, reliable low cost scope. Reviews keep producing 1 word. Unbelievable!

Available Sizes:

Cobra 4X32

Cobra 3-9X42AO

Cobra 3-9X50AO

(See p.42 for technical specification)



Firm finger-adjustable turret



Cobra 3-9X42AO



Cobra 3-9X50AO

*Illumination available upon request.

Cobra SERIES

TECHNICAL DATA

	3-9X42AO	3-9X50AO
		
Magnification	3-9X	3-9X
Objective Lens Dia.	42mm	50mm
Linear field of View (ft@100yds)	35.43-13.62	37.34-11.09
Exit Pupil	14mm-4.67mm	10mm-5.38mm
Diopter Adjustment Range (dpt)	-2/+2	-2/+2
Eye relief (inch)	3.75-3.15	4.10-3.19
Parallax-free Setting	25yds-∞	25yds-∞
Adjustment per click (in/100yds)	1/4	1/4
Max. Windage adjustment range	25'	25'
Max. Elevation adjustment range	25'	25'
Tube Diameter (mm)	25.4mm	25.4mm
Illumination	-	-
Length (in/mm)	13.08/332	13.59/345
Weight (oz/g)	18.19/462	21.66/550
Art. No.	37279 (Mil-Dot; Matte Black)	37280 (Mil-Dot; Matte Black)
	Illuminated model available upon request.	

Optisan reserve the right to modify design for continuous product improvement without prior notice.